


WATERPROOFING BY BOSTIK

bostik.com.au



We offer expert training on all of our Construction products, both online and in-person – just ask!



/ Bostik Australia Pty Ltd
Level 1, 6 English Street
Essendon Fields VIC 3041
bostik.com.au



So smart!



BOSTIK'S **NEW** COMPLETE WATERPROOFING SOLUTION

Protect your next job with a complete system of Bostik products. Our advanced waterproofing technologies ensure that your installation is protected from unwanted water penetration where it can cause damage. Product lines featured in our waterproofing range include:

- Waterbased membranes
- Polyurethane membranes
- Cementitious membranes
- Bond breaker tape



SCAN TO LEARN
MORE AT BOSTIK
ACADEMY



 **Bostik**



BOSTIK AUSTRALIA TRADE



BOSTIK TRADE



BOSTIK AUSTRALIA

bostik.com.au

WATER PROOFING SELECTION CHART



/ DAMPFIX INSTANT SEAL

- EASY TO APPLY, SELF-ADHESIVE
- TEAR RESISTANT
- BOND BREAKER IN DAMPFIX MEMBRANE SYSTEM

/ DAMPFIX PLATINUM



ALL-IN-ONE RAPID DRYING CLASS 3 WATERPROOFING MEMBRANE

Suitable for use in internal wet area shower, bathroom, kitchen, laundry & toilet areas, external balconies, rooftops & podium levels, planter boxes, retaining walls, swimming pools and exposed waterproofing membrane to external applications subjected to light pedestrian traffic only.

- RAPID DRYING
- UV RESISTANT
- CONTAINS ROOT INHIBITORS THAT REPELS ROOT GROWTH IN PLANTER BOXES

COMES IN:
● GREY

/ DAMPFIX GOLD



READY-TO-USE, HIGHLY ELASTIC, CLASS 3 WATERPROOFING MEMBRANE

Specifically formulated for application on graded substrates that provide positive falls to drainage outlets. All applications to be covered by tile or other surface wearing and protective systems.

- FIBRE REINFORCED
- HIGH RESISTANCE TO DETERGENTS & BLEACH
- DOES NOT EMBRITTLE WITH AGE

COMES IN:
● GREY ● GOLD

/ DAMPFIX PU



HIGHLY ELASTIC, CLASS 3, POLYURETHANE WATERPROOFING MEMBRANE

Specifically formulated for applications where the waterproofing membrane is to be covered by tiling systems laid on an unbonded reinforced screed to falls.

- TOUGH ELASTOMERIC MEMBRANE WHEN CURED
- DOES NOT CONTAIN BITUMEN
- WILL NOT BLEED THROUGH POROUS MATERIALS SUCH AS MARBLE, NATURAL STONE AND SLATE TILES

COMES IN:
● GREY

/ DAMPFIX 1K



ONE COMPONENT, FLEXIBLE, FIBRE-REINFORCED CEMENTITIOUS WATERPROOFING MEMBRANE

Specifically formulated to withstands both negative and positive hydrostatic pressure to 5 bars (50 Meters). Application areas include internal wet area shower, bathroom and laundry; to external balconies, retaining walls, planter boxes, rooftops & podium levels.

- RAPID DRYING
- BRUSH, TROWEL, ROLLER OR SPRAY APPLICATION
- APPROVED FOR DIRECT CONTACT WITH POTABLE WATER (AS4020:2005)

/ DAMPFIX IMMERSSED A+B



TWO COMPONENT WATER BASED, ACRYLIC MODIFIED CEMENT-BASED WATERPROOFING MEMBRANE

Bostik Dampfix Immersed Waterproofing Membrane is suitable for use in immersed applications such as pools and spas.

- FAST DRYING
- CAN BE APPLIED TO DAMP SUBSTRATES
- 2 COMPONENT SYSTEM

INTERNAL WET AREA (e.g. Shower, bathroom, kitchen, laundry, toilet areas)					
EXTERNAL – COVERED (i.e. Under tiles) (e.g. Balconies)					
EXTERNAL – EXPOSED* (e.g. Rooftops, facades) *Light foot traffic only					
PLANTER BOXES					
RETAINING WALLS					
SUBMERGED APPLICATIONS UNDER TILES (e.g. Swimming pools, spas)					
MEMBRANE RATING (AS 4654 .1 & AS/NZS4858)	Class 3	Class 3	Class 3* (AS 4654)	Class 1	Class 1 / 2
DRY TIME PER COAT @ 22°C/50% RH	1-2 hrs	2 hrs	24 hrs	1-2 hrs	1-2 hrs
DRY TIME FOLLOWING TRADE @ 22°C/50% RH	4-6 hrs	24 hrs	72 hrs	24 hrs	4 hrs
HYDROSTATIC PRESSURE (POSITIVE & NEGATIVE)					
TENSILE STRENGTH (7 DAYS)	≥ 2.0 MPa	1.5-2.0 MPa	≥ 2.0 MPa	≥ 2.0 MPa	≥ 1.5 MPa
CONSUMPTION PER COAT	Floors: 20 m ² per 15L Wall: 30 m ² per 15L	Floors: 20 m ² per 15L Wall: 30 m ² per 15L	20 m ² per 15L	1.2 kg/m ² /mm	Floors: 40 m ² per kit Wall: 50 m ² per kit